

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 23\_BNC-50-0-16/133\_N

Rev.: B



### Description

Straight panel receptacle jack, flange mount

Interface standards  
IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 4 GHz

#### Mechanical Data

Weight 0.0101 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00010119
Catalogue drawing	DCA-00010121
Mounting hole	DOU-00009051

### Ordering Information

Bulk 100 pcs package	23_BNC-50-0-16/133_NH
Single package	23_BNC-50-0-16/133_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**

Document: DOC-0000187345 I

Issued: 25.10.07

Uncontrolled Copy

Page 1/1