

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_SMC-50-0-2/111_N

Rev.: B



Description

Straight bulkhead receptacle jack

Interface standards
IEC 60169-9_MIL-STD-348A/312_CECC 22140



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 10 GHz

Mechanical Data

Weight 0.0016 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Piece Parts	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Fastening nut	Brass
Washer	Bronze

Surface Plating

Centre contact	Gold Plating (Nickel underplated)
Outer contact	Gold Plating (Nickel underplated)
Body	Gold Plating (Nickel underplated)
Fastening nut	Gold Plating (Nickel underplated)
Washer	Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00010412
Catalogue drawing	DCA-00010414
Mounting hole	DOU-00008855

Ordering Information

Single package	22_SMC-50-0-2/111_NE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com