

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_SMA-50-0-53/199_N

Rev.: B



Description

Straight bulkhead receptacle jack

Interface standards
IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Weight 0.0019 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Fastening nut
Washer

Material

Copper Beryllium Alloy
Stainless Steel
Stainless Steel
PFA / PTFE
Stainless Steel
Bronze

Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

Related Documents

Catalogue drawing DCA-00010437
Mounting hole DOU-00010146

Ordering Information

Single package 22_SMA-50-0-53/199_NE
Bulk 100 pcs package 22_SMA-50-0-53/199_NH

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions