

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_SMA-50-0-12/111\_N

Rev.: G



### Description

Straight bulkhead receptacle jack

Interface standards  
IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Weight 0.0031 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) not compliant

#### Material Data

##### Piece Parts

Piece Parts	Material
Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Copper Beryllium Alloy
Insulator	PFA / PTFE
Gasket	FPM

##### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)

### Related Documents

Catalogue drawing DCA-00011406  
Mounting hole DOU-00010146

### Ordering Information

Tray package 22\_SMA-50-0-12/111\_NY  
Single package 22\_SMA-50-0-12/111\_NE

### Remarks

Hermetically sealed: leakrate 10<sup>-6</sup> Torr/l/sec (atm cc/s)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**