

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_BNC-50-0-24/100_N

Rev.: I



Description

Straight bulkhead receptacle jack

Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 4 GHz

Mechanical Data

Weight 0.0131 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) not compliant

Material Data

Piece Parts

Piece Parts	Material
Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	MVQ (Silicone Rubber)
Fastening nut	Brass
Washer	Bronze

Surface Plating

Centre contact	Gold Plating (Nickel underplated)
Outer contact	Silver Plating
Body	Silver Plating
Fastening nut	Silver Plating
Washer	Silver Plating

Related Documents

Outline drawing	DOU-00011233
Catalogue drawing	DCA-00011235
Mounting hole	DOU-00008762

Ordering Information

Single package 22_BNC-50-0-24/100_NE

Remarks

Hermetically sealed

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions