





APA-324-G-A



APA-318-G-J



APA-640-T-P

**MOLD-TO-POSITION PRODUCT**  
Minimums or set-up charges may apply. Call Samtec.

(2,54mm) .100"

APA SERIES

# AUTOMATED INSERTION ADAPTOR PLUGS

Mates with:  
ICO, ICA

## FEATURES

- Side & end stackable
- Great for auto insertion
- Open body design

## SPECIFICATIONS

For complete specifications see [www.samtec.com?APA](http://www.samtec.com?APA)

### Insulator Material:

Black Glass Filled Polyester except -328 is LCP



### Flammability Rating:

UL 94V-O

### Insulation Resistance:

5000 MΩ min

### Operating Temp Range:

-55°C to +105°C with Tin;

-55°C to +125°C with Gold.

### Withstanding Voltage:

1000 VRMS

### Terminal Material:

Brass except styles -M, -N and -P are Phosphor Bronze or Brass

### Plating:

Au over 50μ" (1,27mm) Ni or Sn over 100μ" (2,54mm) Cu or 50μ" (1,27mm) Ni

### Current Rating:

1 A

### Terminal Retention in Body:

5 lbs (22,25N) against barb

**APA**

**ROW SPACING & NO. OF PINS**

**PLATING OPTION**

**LEAD STYLE**

Specify from chart below

**-G**  
= 20μ" (0,58μm) Gold

**-T**  
= Tin

**-A or -A1**  
= Round Pin

STYLE	X DIA
-A	(0,64) .025
-A1	(0,46) .018

Style A Component No. = T-1R0-  
Style A1 Component No. = T-1R5-

**-J**  
= Solder Shell

Component No. = S-1P1-

**-M, -N or -P**  
= Interconnect Post

STYLE	Y
-M	(1,52) .060
-N	(4,69) .185
-P	(11,05) .435

Not available with -328 body.  
Component No. = T-1R14-

	Row Space	No. of Pins	
-308	.300 (7,62)	08	
-314		14	
-316		16	
-318		18	
-320		20	
-322*		22	
-324		24	
-328		28	
-422		.400 (10,16)	22
-624		.600 (15,24)	24
-628	28		
-632	32		
-640	40		
-648	48		

\*-322 has no cross bar on one end.

**Note:**  
Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600  
 SAMTEC INDIA • Tel: +91-90-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109  
 SAMTEC HONG KONG • Tel: 852-26009858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112