





APA-324-G-A



APA-318-G-J



APA-640-T-P

**MOLD-TO-POSITION PRODUCT**  
Minimums or set-up charges may apply. Call Samtec.

(2,54mm) .100"

APA SERIES

# AUTOMATED INSERTION ADAPTOR PLUGS

Mates with:  
ICO, ICA

## FEATURES

- Side & end stackable
- Great for auto insertion
- Open body design

## SPECIFICATIONS

For complete specifications see [www.samtec.com?APA](http://www.samtec.com?APA)

**Insulator Material:**

Black Glass Filled Polyester except -328 is LCP



**Flammability Rating:**  
UL 94V-O

**Insulation Resistance:**  
5000 MΩ min

**Operating Temp Range:**  
-55°C to +105°C with Tin;  
-55°C to +125°C with Gold.

**Withstanding Voltage:**  
1000 VRMS

**Terminal Material:**

Brass except styles -M, -N and -P are Phosphor Bronze or Brass

**Plating:**

Au over 50µ" (1,27mm) Ni or Sn over 100µ" (2,54mm) Cu or 50µ" (1,27mm) Ni

**Current Rating:**

1 A

**Terminal Retention in Body:**  
5 lbs (22,25N) against barb

APA

ROW SPACING & NO. OF PINS

PLATING OPTION

LEAD STYLE

**Specify from chart below**

	Row Space	No. of Pins	
-308	.300 (7,62)	08	
-314		14	
-316		16	
-318		18	
-320		20	
-322*		22	
-324		24	
-328		28	
-422		.400 (10,16)	22
-624		.600 (15,24)	24
-628	28		
-632	32		
-640	40		
-648	48		

\*-322 has no cross bar on one end.

-A or -A1  
= Round Pin

STYLE	X DIA
-A	(0,64) .025
-A1	(0,46) .018

Style A Component No. = T-1R0-  
Style A1 Component No. = T-1R5-

-J  
= Solder Shell

Component No. = S-1P1-

-M, -N or -P  
= Interconnect Post

STYLE	Y
-M	(1,52) .060
-N	(4,69) .185
-P	(11,05) .435

Not available with -328 body.  
Component No. = T-1R14-

**Note:**  
Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733    SAMTEC SILICON VALLEY • Tel: 408-395-5900    SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227    SAMTEC UNITED KINGDOM • Tel: 44 01236 739292    SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60    SAMTEC ITALY • Tel: 39 039 8890337    SAMTEC NORDIC/BALTIC • Tel: +46-84477280    SAMTEC BENELUX • Tel: 44 01236 739292    SAMTEC ISRAEL • Tel: 972-3-7526600  
 SAMTEC INDIA • Tel: +91-90-3272 1612    SAMTEC ASIA PACIFIC • Tel: 65 6745-5955    SAMTEC JAPAN • Tel: 045-475-1385    SAMTEC CHINA • Tel: 86-21-61103766    SAMTEC TAIWAN • Tel: 886-2-2735-6109  
 SAMTEC HONG KONG • Tel: 852-26009858    SAMTEC KOREA • Tel: 82-31-717-5685    SAMTEC ANZ • Tel: 613 9512 7747    SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112