


## 1674506 -1 Product Details

**Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



1674506 -1

[Active](#)

### Memory Sockets

[Always ELV Compliant](#) ( [Find RoHS Compliant Alternates / Statement of Compliance](#) )

#### Product Highlights:

- ? Fax Modem Socket
- ? Gold Flash Contact Mating Area Plating
- ? Number of Positions = 124
- ? .80 mm Centerline
- ? Stack Height = 4.00 mm

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- ? [SEMI-HARD TRAY ASSY 0.8mm PITCH FAX MODEM SOCKET 124...](#) (PDF, Japanese)

#### Catalog Pages/Data Sheets:

- ? None Available

#### Product Specifications:

- ? [0.8mm Pitch Faxmodem Socket](#) (PDF, English)

#### Application Specifications:

- ? None Available

#### Instruction Sheets:

- ? [0.8mm Pitch Faxmodem Socket](#) (PDF, English)

#### CAD Files:

- ? None Available

#### Additional Information:

- ? [Product Line Information](#)

#### Related Products:

- ? [Tooling](#)

[List all Documents](#)

### Product Features

(Please use the Product Drawing for all design activity)

#### Product Type Features:

- ? Product Type = Fax Modem Socket
- ? [Number of Positions](#) = 124
- ? [Module Orientation](#) = Right Angle
- ? Comment = Without Locating Boss/Peg/Post(s)

#### Termination Related Features:

- ? Solder Tail Contact Plating = Gold Flash

#### Body Related Features:

- ? [Centerline \(mm \[in\]\)](#) = 0.80 [0.031]
- ? [Number of Rows](#) = Dual
- ? [Ejector Location](#) = None
- ? Latch Material = Stainless Steel
- ? Latch Plating = Tin -lead

#### Contact Related Features:

- ? Contact Mating Area Plating = Gold Flash
- ? [Contact Mount](#) = Surface Mount
- ? Contact Material = Phosphor Bronze

#### Housing Related Features:

- ? Housing Material = Thermoplastic High Temperature
- ? Housing Color = Black
- ? Housing Flammability Rating = UL 94V -0

#### Configuration Related Features:

- ? Stack Height (mm [in]) = 4.00 [0.157]
- ? [Insertion Style](#) = Cam -In

#### Industry Standards:

- ? [RoHS/ELV Compliance](#) = ELV compliant
- ? [Lead Free Solder Processes](#) = Reflow solder capable to 245°C
- ? RoHS/ELV Compliance History = Always was ELV compliant

#### Packaging Related Features:

- ? Packaging Method = Tray
- ? Packaging Quantity = 20

#### Other:

- ? Brand = AMP