


1473149 -1 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



1473149 -1

[Active](#)

Memory Sockets

[Converted to EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? SO DIMM
- ? Gold Flash Contact Mating Area Plating
- ? Number of Positions = 200
- ? DRAM Type = Double Data Rate (DDR)
- ? DRAM Voltage = 2.5 V

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> ? DDR1 & DDR2 SODIMM SOCKET 0.6mm PITCH 200POS STANDAR... (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> ? DDR S.O.DIMM Socket 200 Positions (PDF, English) <p>Application Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>CAD Files: (CAD Format & Compression Information)</p> <ul style="list-style-type: none"> ? 2D Drawing (DXF, Version K) ? 3D Model (IGES, Version K) ? 3D Model (STEP, Version K) <p style="text-align: right;">List all Documents</p>	<p>Additional Information:</p> <ul style="list-style-type: none"> ? Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ? Tooling

Product Features <small>(Please use the Product Drawing for all design activity)</small>	
<p>Product Type Features:</p> <ul style="list-style-type: none"> ? Product Type = SO DIMM ? Number of Positions = 200 ? DRAM Type = Double Data Rate (DDR) ? Module Orientation = Right Angle ? Profile = Standard <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> ? Keying = Reverse <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> ? DRAM Voltage = 2.5 V <p>Termination Related Features:</p> <ul style="list-style-type: none"> ? Solder Tail Contact Plating = Gold Flash <p>Body Related Features:</p> <ul style="list-style-type: none"> ? Row-to-Row Spacing (mm [in]) = 6.20 [0.244] ? Centerline (mm [in]) = 0.60 [0.024] ? Number of Rows = Dual ? Ejector Type = Locking ? Ejector Location = Both Ends ? Number of Keys = 1 ? Latch Material = Stainless Steel ? Latch Plating = Tin ? Boss = With <p>Contact Related Features:</p> <ul style="list-style-type: none"> ? Contact Mating Area Plating = Gold Flash ? Contact Mount = Surface Mount ? Contact Material = Copper Alloy 	<p>Housing Related Features:</p> <ul style="list-style-type: none"> ? Housing Material = Thermoplastic High Temperature ? Housing Color = Black ? Housing Flammability Rating = UL 94V -0 <p>Configuration Related Features:</p> <ul style="list-style-type: none"> ? Stack Height (mm [in]) = 5.20 [0.205] ? Insertion Style = Cam -In ? Center Key (mm [in]) = None <p>Industry Standards:</p> <ul style="list-style-type: none"> ? RoHS/ELV Compliance = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C ? RoHS/ELV Compliance History = Converted to comply with RoHS directive <p>Operation/Application:</p> <ul style="list-style-type: none"> ? Application Type = DDR SDRAM <p>Packaging Related Features:</p> <ul style="list-style-type: none"> ? Packaging Method = Semi - Hard Tray Assembly ? Packaging Quantity = 20 Pieces/Tray <p>Other:</p> <ul style="list-style-type: none"> ? Brand = AMP