

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 16\_716-50-12-11/003\_-

Rev.: C.00 

### Description

Right angle cable plug

QUICK-FIT connector  
For outdoor applications  
Water protection according to IP 68



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
Frequency range	DC to 2.5 GHz      2.5 to 3 GHz
Return loss	≥ 30 dB      ≥ 28 dB
Intermodulation	≤ -155 dBc (2 x 43 dBm carrier)

#### Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.2357 kg

#### Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE / PPO	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	MVQ (Silicone Rubber)	

#### Related Documents

Outline drawing	DOU-00006732
Catalogue drawing	DOU-00006734
Assembly instruction	DOC-0000179113

#### Ordering Information

Single package	16_716-50-12-11/003_-E
----------------	------------------------

#### Additional Information

Suitable cables	SUCOFEED_1/2, SUCOFEED_1/2_FR, SUCOFEED_1/2_FR_UL, Heliac LDF4-50A, NK Cables RF 1/2-50, Cellflex LCF12-50
Interface standards	IEC 61169-4_CECC 22190_DIN 47223_VG 95250

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com