

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_BNC-75-4-5/133_N

Rev.: C



Description

Right angle cable plug

Interface Standards
Interface compatible with IEC 61169-8



Technical Data

Electrical Data

Impedance 75 Ω
Interface frequency max. 1 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0166 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Coupling nut
Gasket
Crimp ferrule

Material

Brass
Brass
Brass
PFA / PTFE
Brass
MVQ (Silicone Rubber)
Copper

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00006035
Catalogue drawing DOU-00006037
Assembly instruction DOC-0000179148

Ordering Information

Single package 16_BNC-75-4-5/133_NE

Additional Information

Suitable cable G_04233_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions