

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_BNC-50-3-58/133\_N

Rev.: C



### Description

Straight cable plug

Interface Standards  
IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 4 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0098 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator  
Coupling nut  
Gasket  
Crimp ferrule

##### Material

Brass  
Brass  
Brass  
PFA / PTFE  
Brass  
MVQ (Silicone Rubber)  
Copper

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating  
  
SUCOPLATE (R) Plating  
  
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00071181  
Catalogue drawing DOU-00006196  
Assembly instruction DOC-0000179061

#### Ordering Information

Single package 11\_BNC-50-3-58/133\_NE  
Bulk 100 pcs package 11\_BNC-50-3-58/133\_NH

#### Additional Information

Suitable cable S\_03232-01

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

##### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**