

This document was generated on 02/09/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0950432891 Status: Active Overview: modular_plugs_jacks Description: Modular Plug, Short I Documents: 3D Model Drawing (PDF) Description:		ody, Shielded, 8/8, Black Boot, Cat5	
		Product Specification PS-95043 (PDF) RoHS Certificate of Compliance (PDF)	
Agency Certifica	ation		Seri
CSA		LR19980	image - Reference only
UL		E107635	
0			EU RoHS China RoHS
General			ELV and RoHS
Product Family		Modular Jacks/Plugs	Compliant
Series		95043 Colored Deptilophie to Dive Tangile Strength: 09 0N (22	REACH SVHC Contains SVHC: No
Comments		Colored Boot Cable to Plug Tensile Strength: 98.0N (22	Low-Halogen Status
Component Type		lb) Wire Plug	Not Low-Halogen
Magnetic		No	
Overview		modular_plugs_jacks	Need more information on product
Performance Category		5	environmental compliance?
Power over Ethernet (PoE)		N/A	Email productcompliance@molex.com
Product Name		RJ45	For a multiple part number RoHS Certificate Compliance, <u>click here</u>
Physical			Compliance, <u>click nere</u>
Boot Color		BLACK	Please visit the Contact Us section for any
Color - Resin		Clear	non-product compliance questions.
Durability (mating cycles max)		750	
Flammability		94V-2	
Inverted / Top Latch		N/A	
Lightpipes/LEDs		None	Search Parts in this Series
Material - Metal		Copper Alloy, Phosphor Bronze	<u>95043</u> Series
Material - Plating Ma		Gold	
Material - Plating Termination		Tin	Mates With
Material - Resin		Polycarbonate	FCC 68 Jacks
Orientation		N/A	
PCB Locator		No	Application Tooling FAQ
PCB Retention Packaging Type		None	Tooling specifications and manuals are
Pitch - Mating Interface		Bag 1.02mm (.040")	found by selecting the products below.
Plating min - Mating		0.305µm (12µ")	Crimp Height Specifications are then
Plating min - Termin		1.270µm (50µ")	contained in the Application Tooling
Ports		1.270µm (00µ)	Specification document.
Positions / Loaded Contacts		8/8	Global
Surface Mount Compatible (SMC)		N/A	Description Product #
Temperature Range - Operating		-40°C to +60°C	Parallel Action 0690081100
Termination Interface: Style		IDT or Pierce	Handtool for 95043
Waterproof / Dustproof		No	Shielded Plug, Cat
Wire/Cable Type		Round	5, 8/8 Circuit, Short
Flootrigel			Body Termination 0623001400
Electrical			Machine, Modular
Current - Maximum per Contact		1.5A	Plug
Grounding to Panel		N/A	
Shielded Voltage - Maximum		Yes 125V AC (RMS)/DC	

Material Info

Reference - Drawing Numbers

Application Specification Product Specification Sales Drawing

AS-95043 PS-95043 SDA-95043

This document was generated on 02/09/2011
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION