


Product Details for 5558501 - 1



5558501 - 1

[Active](#)

PCB Mounted Jacks - Single Port, Multi -port and Stacked

[RoHS Compliant \(Statement of Compliance\)](#)

Product Highlights:

- ? Jack
- ? Multiple Port Configuration
- ? 1 x 6 Jack Configuration
- ? Jack Type = RJ45
- ? Number of Positions = 8

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> ? MODULAR JACK ASSEMBLY, 6 PORT, 8 POSITION, RIGHT ANG... (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> ? High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English) <p>Application Specifications:</p> <ul style="list-style-type: none"> ? Modular Jacks (PDF, English) <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>CAD Files:</p> <ul style="list-style-type: none"> ? None Available <p style="text-align: right;">List all Documents</p>	<p>Additional Information:</p> <ul style="list-style-type: none"> ? Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ? Tooling

Product Features <small>(Please use the Product Drawing for all design activity)</small>	
<p>Product Type Features:</p> <ul style="list-style-type: none"> ? Product Type = Jack ? Jack Type = RJ45 ? Number of Positions = 8 ? PCB Mount Angle = Side Entry (Right Angle) ? PCB Mount Style = Thru Hole ? PCB Termination Type = Solder ? Shielded = No ? Performance Category = Cat 5 ? Number of Contacts Loaded = 8 ? Grounding Options = Without ? Panel Stops = Without ? Keyed = No ? Profile = Standard ? IR Reflow Compatible = Yes ? Color = Black ? Comment = Cat 5 solder tail positions for this mod jack do not follow same number sequence as that of the traditional mod jacks. <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> ? Jack Configuration = 1 x 6 ? Panel Attachment = Without <p>Termination Related Features:</p> <ul style="list-style-type: none"> ? Solder Tail Plating = Tin over Nickel 	<p>Body Related Features:</p> <ul style="list-style-type: none"> ? Port Configuration = Multiple ? Inverted Jack Face = No ? LED = Without ? PCB Tail Length (mm [in]) = 3.56 [0.140] ? Number of Contacts Loaded, RJ45 (8 Positions) = 8 <p>Contact Related Features:</p> <ul style="list-style-type: none"> ? Contact Mating Area Plating = Gold (50) over Nickel (50) ? Contact Material = Phosphor Bronze <p>Housing Related Features:</p> <ul style="list-style-type: none"> ? Housing Material = High Temperature Nylon ? Housing Flammability Rating = UL 94V -0 <p>Industry Standards:</p> <ul style="list-style-type: none"> ? RoHS/ELV Compliance = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C ? RoHS/ELV Compliance History = Always was RoHS compliant <p>Packaging Related Features:</p> <ul style="list-style-type: none"> ? Packaging Method = Tray ? Packaging Quantity = 15 <p>Other:</p> <ul style="list-style-type: none"> ? Brand = AMP