


Product Details for 413476 - 6



413476 - 6

[Active](#)

Decoupled BNC RF Connectors

[Not ELV or RoHS Compliant](#) [\(Find RoHS Compliant Alternates\)](#)

Product Highlights:

- ? Terminate To Printed Circuit Board
- ? Connector Impedance = 50 ?
- ? Capacitance = 9,400 pF
- ? Without ESD Protection
- ? Voltage Rating = 1500 VDC

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [JACK, DECOUPLER, VERTICAL, PCB, SERIES BNC](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? [PCB Decoupled BNC Straight & Right Angle Jacks](#) (PDF, English)

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? [PCB Mount Angle](#) = Vertical
- ? [PCB Retention Feature](#) = With
- ? [PCB Retention Method Feature](#) = Mounting Post
- ? [Clip Style](#) = Standard
- ? [Mounting Post Style](#) = Standard
- ? Mounting Post Length (mm [in]) = 4.01 [0.158]
- ? [Dielectric Material](#) = Polymethylpentene
- ? Product Type = Connector
- ? Gender = Jack
- ? Grade = Commercial
- ? Body Material = VALOX

Mechanical Attachment:

- ? [Panel Attachment](#) = With
- ? Panel Attachment Method = Lockwasher and Nut

Electrical Characteristics:

- ? [Connector Impedance \(?\)](#) = 50
- ? [Capacitance \(pF\)](#) = 9,400
- ? [Voltage Rating \(VDC\)](#) = 1500

Body Related Features:

- ? ESD Protection = Without

Contact Related Features:

- ? Center Contact Material = Phosphor Bronze
- ? Center Contact Plating = Gold (30)

Housing Related Features:

- ? Housing Temperature Rating = Standard

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:

- ? [Terminate To](#) = Printed Circuit Board

Other:

- ? Brand = AMP