


- NOTES:
- RECOMMENDED P.C.B. THICKNESS 1.60 MM
 - HOUSING MAT'L: NYLON 66, 25% GLASS REINFORCED, COLOR: GRAY
 - CONTACTS: PHOS BRONZE ALLOY UNS-C51000, ϕ 0.460 ROUND WIRE, PLATING SEE TABLE.
 - METAL SHELL MATERIAL: COPPER ALLOY, 0.20MM THICK. FINISH: FOR 94927-XXX, TIN-LEAD, 100u" THICK MIN. FOR 94927-XXXLF, PURE BRIGHT TIN 80u" THICK MIN.
 - INSULATED TAPE: 3M COMPANY TAPE #5
 - PACKAGING PER GES-14-361, USING TUBE
 - IF LF P/N THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
 - THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.60mm MINIMUM THICK CIRCUIT BOARD.
 - IF LF P/N PACKAGING MEETS GS-14-920 SPECIFICATION.

PRODUCT NO	NUMBER OF POS.	LOADED POSITION	PLATING
94927-088	8	ALL POS.	30u" G.X.T.
94927-088LF			



mat'l code		tolerance unless otherwise specified		CUSTOMER COPY		FCI		www.fciconnect.com		
rev.	ecm no.	dr	date	linear	.0 ± 0.25	projection	title	product family	MOD JACK	code
A	T50230	CL	08/11/95		.00 ± 0.13	A3	LOW PROFILE PCB III 8 POS MOD JACK, FULLY SHIELDED	size	dwg no.	TWN
B	T50286	CL	10/20/95		.000 ± 0.05					
C	T03-0443	WL	10/06/03	angles	± 2'	scale	94927	sheet	1 OF 1	
D	N05-0030	YS	02/05/05	dr	C L FENG D3/06/95	unit				
				enagr	TONY CHIEN D3/06/95	mm /inch				
				chr	TONY CHIEN D3/06/95	3 : 1				
				pppd	JENN TSAO D3/06/95					
sheet	revision	D								
index	sheet	1								