

6368034-2 Product Details[Live Product Chat](#)**6368034-2**

TE Internal Number: 6368034-

2

 **Active**[View 3D PDF](#)**PCB Mounted Jacks - Single Port, Multi-port and Stacked** [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)**Product Highlights:**

- Jack
- Stacked Port Configuration
- 2 x 6 Jack Configuration
- Jack Type = RJ45
- Number of Positions = 8

[View all Features](#)**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)
Documentation & Additional Information**Product Drawings:**

- [STACKED MODULAR JACK ASSEMBLY, 2X6 OFFSET, 8 POSN, R...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [High Performance Modular Plugs & Jacks, PCB Mounted](#) (PDF, English)

Application Specifications:

- [Modular Jacks](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version A)
- [3D Model](#) (IGES, Version A)
- [3D Model](#) (STEP, Version A)

[List all Documents](#)**Additional Information:**

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- [Product Type](#) = Jack
- [Jack Type](#) = RJ45
- [Number of Positions](#) = 8
- [PCB Mount Angle](#) = Side Entry (Right Angle)
- [PCB Mount Style](#) = Through Hole
- [PCB Termination Type](#) = Press-Fit
- [Shielded](#) = Yes
- [Performance Category](#) = Cat 5
- Number of Contacts Loaded = 8
- [Grounding Options](#) = Panel Ground and PCB Ground
- [Panel Stops](#) = Without
- [Keyed](#) = No
- [Profile](#) = Very Low; Offset - Over Hangs PCB
- [Color](#) = Black
- Number of Terminals Per Port = 8
- Shield Material = .010 [0.25] Copper Alloy
- PCB Thickness (mm [in]) = 1.57 [0.062]

Mechanical Attachment:

- [Jack Configuration](#) = 2 x 6
- [Panel Attachment](#) = Without

Termination Related Features:

- [Solder Tail Contact Plating](#) = Tin over Nickel
- Grounding Clips = With

Body Related Features:

- Port Configuration = Stacked
- [Inverted Jack Face](#) = No
- [LED](#) = Without
- Shield Plating = Tin over Copper
- Number of PCB Ground Tabs = 9
- [PCB Tail Length \(mm \[in\]\)](#) = 4.35 [0.171]
- Grounding Tab Plating = Tin over Copper

Contact Related Features:

- [Contact Mating Area Plating Material](#) = Gold (50)
- Contact Base Material = Phosphor Bronze
- PCB ACTION PIN Grounds = Without

Housing Related Features:

- Housing Material = Polyester (PBT)
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

Configuration Related Features:

- Number of Grounding Clips = 6

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = AMP