



MODS-D, MODS-E SERIES

SINGLE VERTICAL & SMT MODULAR JACKS

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?MODS-D

Insulator Material: Nylon 46/ PBT Glass Filled (Nylon for -SM, PBT for -TH)
Contact Material: Phosphor Bronze
Shield Material: Copper Alloy
Plating: Gold on Contacts, Nickel on Shield, Tin on Tails
Operating Temp Range: -25°C to +90°C
Current Rating: 1.5 A per contact
Voltage Rating: 120 VAC
Contact Resistance: 20 mΩ max
Minimum Cycles: 500
System Applications: CAT3
Packaging: Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.
RoHS Compliant: Yes
Lead-Free Solderable: -SM=Yes -TH=Yes (Wave Solder only)



MODS	D	POSITIONS CONTACTS	PLATING	SHIELD OPTION	TAIL
-6P4C = 6 Positions 4 Contacts		-L = 15µ" (0,38 µm) Gold on Mating Area, Gold Flash on Tails		(Leave Blank for Unshielded)	-SM = Surface Mount
-6P6C = 6 Positions 6 Contacts		-U = 50µ" (1,27µm) Gold on Mating Area, Gold Flash on Tails		-S = Shielded	-TH = Through-hole
-8P8C = 8 Positions 8 Contacts				-N = No Panel Stops (Unshielded Only)	

POSITIONS CONTACTS	A	B	B (-S)
-6PXC	(15,90) .626	(13,30) .524	(14,10) .555
-8P8C	(17,80) .701	(15,20) .598	(16,00) .630

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?MODS-E

Insulator Material: PBT Glass Filled
Contact Material: Phosphor Bronze
Shield Material: Copper Alloy
Plating: Gold on Contacts, Nickel on Shield
Operating Temp Range: -25°C to +90°C
Current Rating: 1.5 A per contact
Voltage Rating: 120 VAC
Contact Resistance: 20 mΩ max
Minimum Cycles: 500
System Applications: CAT3
Packaging: Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.
RoHS Compliant: Yes
Lead-Free Solderable: Yes (Wave Solder only)



MODS	E	POSITIONS CONTACTS	PLATING	SHIELD OPTION
-4P4C = 4 Positions 4 Contacts		Unshielded Only		(Leave Blank for Unshielded)
-6P4C = 6 Positions 4 Contacts		-G = 15µ" (0,38 µm) Gold on Mating Area, Gold Flash on Tails		-S = Shielded (-4P4C and Panel Stops N/A)
-6P6C = 6 Positions 6 Contacts		-E = 50µ" (1,27µm) Gold on Mating Area, Gold Flash on Tails		
-8P8C = 8 Positions 8 Contacts		Shielded Only		
		-L = 15µ" (0,38 µm) Gold on Mating Area, Gold Flash on Tails		
		-U = 50µ" (1,27µm) Gold on Mating Area, Gold Flash on Tails		

POSITIONS CONTACTS	A	B
-4P4C	(13,80) .543	(11,43) .450
-6PXC	(15,90) .626	(13,46) .530
-8P8C	(17,90) .705	(15,50) .610

APPLICATION SPECIFIC OPTION

- No panel stop option available
- Other plating options available
- Call Samtec.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8990337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109
 Downloaded from Elcodis.com electroSAMTEC HONG KONG • Tel: 852-2680-8558 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112