


**Product Details for 1368035 -3**



**1368035 -3**

[Active](#)

**PCB Mounted Jacks - Single Port, Multi port and Stacked**

[RoHS/Not ELV Compliant](#) (Find RoHS Compliant Alternates/Compliance Statement)

**Product Highlights:**

- ? Jack
  - ? Stacked Port Configuration
  - ? 2 x 6 Jack Configuration
  - ? Jack Type = RJ45
  - ? Number of Positions = 8
- [View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [STACKED MODULAR JACK ASSEMBLY 2 X 6 OFFSET, W/LEDS, ...](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? [High Performance Modular Plugs & Jacks, PCB Mounted](#) (PDF, English)
- ? [Offset Stacked Modular Jack with LED\\_s, Category 5](#) (PDF, English)

**Application Specifications:**

- ? [Modular Jacks](#) (PDF, English)
- ? [Category 5 Shielded Offset Stacked Modular Jack Asse...](#) (PDF, English)

**Instruction Sheets:**

- ? None Available

**CAD Files:** ([CAD Format & Compression Information](#))

- ? [3D Model](#) (IGES, Version 0)

[List all Documents](#)

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

**Product Features** (Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? [Product Type](#) = Jack
- ? [Jack Type](#) = RJ45
- ? [Number of Positions](#) = 8
- ? [PCB Mount Angle](#) = Side Entry (Right Angle)
- ? [PCB Mount Style](#) = Thru Hole
- ? [PCB Termination Type](#) = Press -Fit
- ? [Shielded](#) = Yes
- ? [Performance Category](#) = Cat 5
- ? Number of Contacts Loaded = 8
- ? [Grounding Options](#) = Panel Ground and PCB Ground
- ? [Panel Stops](#) = Without
- ? [Keyed](#) = No
- ? [Profile](#) = Very Low; Offset - Over Hangs PCB
- ? IR Reflow Compatible = No
- ? [Color](#) = Black
- ? Number of Terminals Per Port = 8
- ? Shield Material = .010 [0.25] Copper Alloy
- ? PCB Thickness (mm [in]) = 1.57 [0.062]

**Mechanical Attachment:**

- ? [Jack Configuration](#) = 2 x 6
- ? [Panel Attachment](#) = Without

**Termination Related Features:**

- ? [Solder Tail Plating](#) = Tin -Lead over Nickel
- ? Grounding Clips = Without

**Body Related Features:**

- ? Port Configuration = Stacked
- ? [Inverted Jack Face](#) = No
- ? [LED](#) = With
- ? Shield Plating = Bright Tin over Nickel
- ? Number of PCB Ground Tabs = 9
- ? [PCB Tail Length \(mm \[in\]\)](#) = 4.35 [0.171]
- ? Grounding Tab Plating = Tin -Lead over Copper

**Contact Related Features:**

- ? [Contact Mating Area Plating](#) = Gold (50) over Nickel (50)
- ? Contact Material = Phosphor Bronze
- ? PCB ACTION PIN Grounds = Without

**Housing Related Features:**

- ? Housing Material = Polyester (PBT)
- ? Housing Color = Black
- ? Housing Flammability Rating = UL 94V -0

**Industry Standards:**

- ? [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- ? [Lead Free Solder Processes](#) = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS not ELV compliant

**Identification Marking:**

- ? [LED Color: Top Left](#) = Green/Yellow
- ? [LED Color: Top Right](#) = Green/Yellow
- ? [LED Color: Bottom Left](#) = Green/Yellow
- ? [LED Color: Bottom Right](#) = Green/Yellow

**Other:**

- ? Brand = AMP