

## VIP-2/SC/PDM-2/32

Order No.: 2315272



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2315272>

VARIOFACE module, with two equipotential busbars (P1, P2) for potential distribution, for mounting on NS 35/7.5 or NS 32. Module width: 90.8 mm



Commercial data	
EAN	4046356313094
Pack	1 pcs.
Customs tariff	85369010
Weight/Piece	0.1897 KG
Catalog page information	Page 296 (IF-2009)

#### Product notes

WEEE/RoHS-compliant since:  
09/02/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Nominal voltage $U_N$	250 V AC/DC
Maximum total current per potential	15 A
Potential connections	Per potential (P1, P2) 2 power/16 distributor terminal blocks
Width	90.8 mm

Height	50 mm
Depth	65.5 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Pollution degree	2
Surge voltage category	III

#### Connection data, supply

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	6 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	10
Type of connection	Screw connection
Stripping length	8 mm
Screw thread	M 3

#### Connection data, distribution

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Type of connection	Screw connection
Stripping length	8 mm
Screw thread	M 3

#### Certificates / Approvals



Certification CSA, CUL, UL

**CSA**

Comments	Output
Nominal voltage $U_N$	250 V
Nominal current $I_N$	12 A
AWG/kcmil	30-12
Comments	Input
Nominal voltage $U_N$	250 V
Nominal current $I_N$	12 A
AWG/kcmil	30-10

**CUL**

Comments	Output
Nominal voltage $U_N$	250 V
Nominal current $I_N$	12 A
AWG/kcmil	30-12
Comments	Input
Nominal voltage $U_N$	250 V
Nominal current $I_N$	12 A
AWG/kcmil	30-10



**UL**

Comments	Output
Nominal voltage $U_N$	250 V
Nominal current $I_N$	12 A
AWG/kcmil	30-12
Comments	Input
Nominal voltage $U_N$	250 V
Nominal current $I_N$	12 A
AWG/kcmil	30-10

## Diagrams/Drawings

Circuit diagram

---



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;