



2-12 poles, Spacing 5.08 mm  
insert required no. of poles **X**  
How to order see page 5

2-12 poles, Spacing 5.08 mm  
insert required no. of poles **X**  
How to order see page 5



300 V  
15 A  
AWG 22-14  
250 V  
24 A (T60)  
2.5 mm<sup>2</sup>  
2.0 kV  
0.5 Nm/M3

2.5 mm<sup>2</sup>  
1.5 mm<sup>2</sup>  
1.5 mm<sup>2</sup>

5.08 mm  
1.3 mm  
7.0 mm

PA  
UL94 V-0  
-30°C/+105°C  
CuZn  
Stainless Steel



### Ratings:

Rated Voltage	300 V	250 V
Rated Current	15 A	24 A (T60)
Wire Size	AWG 22-14	2.5 mm <sup>2</sup>
Test Voltage		2.0 kV
Rated Torque/ScrewSize		0.5 Nm/M3

### Max. Rated Cross Section

Single Wire (solid)	2.5 mm <sup>2</sup>
Stranded Wire (flexible)	1.5 mm <sup>2</sup>
Stranded wire with Ferrules	1.5 mm <sup>2</sup>

### Dimensions

Spacing	5.08 mm
PCB Hole Diameter	1.3 mm
Stripped Length	6.0 mm

### Materials

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Terminal Block	CuZn
Wire Guard	Stainless Steel

### Color

Blue

