



2-12 poles, Spacing 5.0 mm
insert required no. of poles **X**
How to order see page 5

2-12 poles, Spacing 5.0 mm
insert required no. of poles **X**
How to order see page 5



300V
15 A
AWG 22-14

250 V
32 A (T60)
4.0 mm²
2.0 kV
0.8 Nm/M3

4.0 mm²
2.5 mm²
1.5 mm²

5.0 mm
2.0 mm x 2.8 mm
7.0 mm

PA
UL94 V-0
-30°C/+105°C
CuZn
Stainless Steel



Ratings:

Rated Voltage
Rated Current
Wire Size
Test Voltage
Rated Torque/ScrewSize

300V
15 A
AWG 22-14
250 V
24 A (T60)
2.5 mm²
2.0 kV
0.5 Nm/M3

Max. Rated Cross Section

Single Wire (solid)
Stranded Wire (flexible)
Stranded wire with Ferrules

2.5 mm²
1.5 mm²
1.5 mm²

Dimensions

Spacing
PCB Hole Diameter
Stripped Length

5.0 mm
1.3 mm
6.0 mm

Materials

Insulating Material
Flammability Class
Temperature Range
Terminal Block
Wire Guard

PA
UL94 V-0
-30°C/+105°C
CuZn
Stainless Steel

Color

Blue

