

**ZFK3DSA 1,5-6,08**

Order No.: 1704554

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1704554>

PC terminal block, Nominal current: 12 A, Nom. voltage: 250 V, Pitch:  
5.08 mm, Number of positions: 1, Type of connection: Spring-cage  
connection, Conductor/PCB connection direction: 45 °

**Commercial data**

EAN	4017918125851
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.00588 KG
Catalog page information	Page 101 (CC-2009)

**Product notes**

WEEE/RoHS-compliant since:  
01/01/2003



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Certificates / Approvals**

Certification

CUL, UL

**CUL**

Nominal voltage $U_N$	300 V
Nominal current $I_N$	10 A
AWG/kcmil	26-12

**UL**

Nominal voltage $U_N$	300 V
Nominal current $I_N$	10 A
AWG/kcmil	26-12

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;