



MATERIAL: COPPER  
 .031" NOM. THICKNESS  
 FINISH: ELECTRO-TIN PLATING

MWID= MAX. WIRE INSULATION DIA.  
 PART NUMBERS ARE FOR LOOSE PIECE TO ORDER PARTS ON TAPE ADD A "T" TO END OF PART NUMBER

MATERIAL NO.	ENGR NO.	WIRE RANGE AWG	DIAMETER "D"	MAX. "L"	±.01 "B"	MWID	MIN. I.D.				INSULATION
190340002	A-259X	22-18	.180	.950	.450	.145	.056				PVC
190340005	A-269X	22-18	.156	.890	.450	.145	.056				PVC
190340007	B-279X	16-14	.180	.950	.450	.175	.084				PVC
190340009	B-289X	16-14	.156	.890	.450	.175	.084				PVC

REMOVED TAPE PARTS	EC NO: 2005/04/77	QUALITY SYMBOLS ▽=0 ∇=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM	SCALE 5:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
	DRWNG: SHAECK		2005/05/04	mm	INCH	DRAWN BY EMF	DATE 07/30/93	TITLE INSULKRIMP MALE BULLET SNAP PLUG
	CHKDR: DEBOSS		2005/05/04	4 PLACES ± --- ± ---	3 PLACES ± --- ± ---	CHECKED BY JM	DATE 07/30/93	
	APPR: DEBOSS		2005/05/04	2 PLACES ± --- ± ---	1 PLACE ± --- ± ---	APPROVED BY FP	DATE 07/30/93	MATERIAL NO.
REV	A	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE	MOLEX INCORPORATED		1 OF 1