

THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		.19	
© COPYRIGHT 19		BY AMP INCORPORATED. ALL RIGHTS RESERVED.			
LOC		DIST		REVISONS	
G		86			
P		LTR		DESCRIPTION	
G				REVISED PER 0L20-0217-97	
DATE		DWN		APVO	
04NOV97		DKS		MJS	

1 TIN PL 0.00254[.000100] MIN THK  
PER ASTM B-545

2 NICKEL PL 0.00508[.000200] MIN THK  
PER QQ-N-290

0.79 ± 0.08  
[0.031 ± 0.003]

1.91  
[0.075]  
APPROX

11.53  
[0.454]  
APPROX

11.53  
[0.454]  
APPROX

OBSELETE	△	343°C MAX	1-329656-1-
	△	150°C MAX	329656
FINISH		OPERATING TEMPERATURE	AMP PART NUMBER

AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DK SCHRUM 04NOV97 CHK MJ SPICER 03DEC97 APVO JL MECKLEY 03DEC97		AMP Incorporated Harrisburg, PA 17105-3608	
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		RECOMMENDED OPERATING TEMPERATURE: SEE TABLE		NAME SPLICE, TERMI-FOIL™ WIRE SIZE: 12-10 AWG	
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING: NOT APPLICABLE		SIZE CAGE CODE DRAWING NO	
FOR ORDER ENTRY		1-800-526-5142		ALUMINUM FOIL THICKNESS: 0.76[0.03] MAX		RESTRICTED TO	
AMP 1470-19 REV 11 JUN 97		MATERIAL COPPER PER ASTM B-152 ANNEALED		FINISH SEE TABLE		A3100779 C- 329656	
04-NOV-97 15:46:27 amp26463 /ws/dept1123/dwg1123/u.termi-foil/u.splices		CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1 REV 6	