













0359	0358	0360	0343
 <p>0359-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>	 <p>0358-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>	 <p>0360-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>	 <p>0343-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>
0356	6659	0347	0329
 <p>0356-0-15-XX-34-XX-10-0 Solder mount in 2,59 min. mounting hole Also available on 24mm wide carrier tape: 1,100 parts per 330mm reel. Order as: 0356-0-57-XX-34-XX-10-0</p>	 <p>6659-0-15-XX-34-XX-10-0 Solder mount in 2,59 min. mounting hole</p>	 <p>0347-0-15-XX-34-XX-10-0 Solder mount in 3,05 min. mounting hole</p>	 <p>0329-0-15-XX-34-XX-10-0 Solder mount in 1,91 min. mounting hole. "knock out" bottom.</p>
0814	5059	8360	9359
 <p>0814-0-15-XX-34-XX-04-0 Solder mount in 2,08 min. mounting hole</p>	 <p>5059-0-15-XX-34-XX-04-0 Press-fit in 2,29 mounting hole</p>	 <p>8360-0-15-XX-34-XX-10-0 Press-fit in 2,21 mounting hole</p>	 <p>9359-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>
<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: $\pm 0,13$ DIAMETERS: $\pm 0,05$ ANGLES: $\pm 2^\circ$</p>	<p>ORDER CODE: XXXX - X - 15 - XX - 34 - XX - XX - 0</p> <p>BASIC PART # SPECIFY SHELL FINISH: SPECIFY CONTACT FINISH:</p> <p> 01 5,08µm TIN/LEAD OVER NICKEL 01 5,08µm TIN/LEAD OVER NICKEL</p> <p> 80 5,08µm TIN OVER NICKEL (RoHS) 80 5,08µm TIN OVER NICKEL (RoHS)</p> <p> 15 0,25µm GOLD OVER NICKEL (RoHS) 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p style="text-align: center;">CONTACT #34 CONTACT (DATA ON PAGE 222)</p>		