













0394	0393	0391	9016
 <p><b>0394-0-15-XX-07-XX-10-0</b> Solder mount in 3,05 min. mounting hole</p>	 <p><b>0393-0-15-XX-07-XX-10-0</b> Solder mount in 3,66 min. mounting hole</p>	 <p><b>0391-0-15-XX-07-XX-10-0</b> Solder mount in 4,04 min. mounting hole</p>	 <p><b>9016-0-15-XX-07-XX-10-0</b> Press-fit in 3,33 mounting hole</p>
0493	0490	0616	0387
 <p><b>0493-0-15-XX-07-XX-10-0</b> Press-fit in 3,66 mounting hole</p>	 <p><b>0490-0-15-XX-07-XX-04-0</b> Press-fit in 3,66 mounting hole</p>	 <p><b>0616-0-18-XX-07-XX-10-0</b> Press-fit in 3,66 mounting hole</p>	 <p><b>0387-0-15-XX-07-XX-04-0</b> Solder mount in 1,60 min. mounting hole</p>
0370	4040	0491	9214
 <p><b>0370-0-19-XX-07-XX-10-0</b> #18 Gage crimp barrel</p>	 <p><b>4040-0-19-XX-07-XX-10-0</b> Wire Termination</p>	 <p><b>0491-0-19-XX-07-XX-04-0</b> For use in stackable patch cords</p>	 <p><b>9214-0-15-XX-07-XX-10-0</b> Solder mount in 2,11 min. mounting hole</p>
<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES TOLERANCES ON:</b> LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 1X - XX - 07 - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <ul style="list-style-type: none"> <li>01 5,08µm TIN/LEAD OVER NICKEL</li> <li>◇ 80 5,08µmTIN OVER NICKEL (RoHS)</li> <li>◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>SPECIFY CONTACT FINISH:</b></p> <ul style="list-style-type: none"> <li>01 5,08µm TIN/LEAD OVER NICKEL</li> <li>◇ 80 5,08µm TIN OVER NICKEL (RoHS)</li> <li>◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>CONTACT</b> #07 CONTACT (DATA ON PAGE 225)</p> 