

8467	6192	9553	5531
<p>8467-0-15-XX-21-XX-04-0 Hex press-fit in 0,91 plated thru hole</p>	<p>6192-0-15-XX-21-XX-04-0 Square press-fit in 0,81 plated thru hole</p>	<p>9553-0-15-XX-X1-XX-04-0 Hex press-fit in 1,04 plated thru hole</p>	<p>5531-0-15-XX-21-XX-10-0 Hex press-fit in 1,04 plated thru hole</p>
7553	9407	9462	1147
<p>7553-0-15-XX-11-XX-10-0 Hex press-fit in 1,04 plated thru hole</p>	<p>9407-0-15-XX-11-XX-10-0 Solder mount in 1,02 min. mounting hole</p>	<p>9462-0-15-XX-21-XX-04-0 Hex press-fit in 1,09 plated thru hole</p>	<p>1147-0-18-XX-21-XX-10-0 Press-fit in 1,09 min. mounting hole</p>
3061	0579	8874	0613
<p>3061-0-19-XX-21-XX-10-0 Wire Termination</p>	<p>0579-0-15-XX-X1-XX-10-0 Press-fit in 1,02 mounting hole</p>	<p>8874-0-15-XX-11-XX-10-0 Bottom entry Surface mount</p>	<p>0613-0-15-XX-21-XX-10-0 Press-fit in 1,19 mounting hole</p>
<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - XX - XX - 10 - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p>SPECIFY CONTACT FINISH: →</p> <p>02 2,54µm TIN/LEAD OVER NICKEL ◇ 84 2,54µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p>SELECT CONTACT #11 or #21 CONTACT (DATA ON PAGE 217)</p> <p align="center"></p>		