

| 9808 | 9101 | 5650 | 8679 |
|---|---|---|---|
| | | | |
| 9808-0-15-XX-16-XX-04-0 Press-fit in 1,70 mounting hole | 9101-0-15-XX-16-XX-10-0 Press-fit in 1,70 mounting hole | 5650-0-19-XX-16-XX-10-0 Press-fit in 1,70 mounting hole | 8679-0-15-XX-16-XX-10-0 Solder mount in 1,80 min. mounting hole |

| 8827 | 6021 | 1873 |
|---|---|---|
| | | |
| 8827-0-15-XX-16-XX-04-0 Press-fit in 1,55 mounting hole | 6021-0-15-XX-16-XX-10-0 Solder mount in 1,57 min. mounting hole | 1873-0-15-XX-16-XX-04-0 Press-fit in 1,68 mounting hole |

| | | | |
|--|--|--|--|
| | | | |
|--|--|--|--|

| | |
|--|---|
| <p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p> | <p>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p>SPECIFY CONTACT FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p style="text-align: center;">CONTACT #16 CONTACT (DATA ON PAGE 221)</p> |
|--|---|

