

<h3>4011</h3> <p><b>4011-0-15-XX-30-XX-04-0</b> Press-fit in .057 mounting hole</p>	<h3>1801</h3> <p><b>1801-0-15-XX-30-XX-04-0</b> Press-fit in .057 mounting hole Shell is Ph. Br. Alloy 544 (B2)</p>	<h3>1001</h3> <p><b>1001-0-15-XX-3X-XX-04-0</b> Press-fit in .057 mounting hole</p>	<h3>0156</h3> <p><b>0156-0-18-XX-30-XX-04-0</b> Self-retention socket pin .038-.043 hole prior to soldering</p>
---	---	---	---

<h3>0255</h3> <p><b>0255-0-15-XX-30-XX-04-0</b> Solder mount in .022 min. mounting hole</p>	<h3>1109</h3> <p><b>1109-0-15-XX-30-XX-04-0</b> Hex press-fit in .057 plated thru hole</p>	<h3>3013</h3> <p><b>3013-0-15-XX-32-XX-04-0</b> Press-fit in .057 mounting hole</p>	<h3>0134</h3> <p><b>0134-0-15-XX-3X-XX-04-0</b> Press-fit in .057 mounting hole</p>
---	--	---	---

<h3>0132/0135</h3> <p><b>013X-0-15-XX-30-XX-04-0</b> Press-fit in .057 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0132-0</td> <td>.273</td> </tr> <tr> <td>0135-0</td> <td>.183</td> </tr> </tbody> </table>	Basic Part Number	Length A	0132-0	.273	0135-0	.183	<h3>0133/0147</h3> <p><b>01XX-0-15-XX-30-XX-04-0</b> Press-fit in .059 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0133-0</td> <td>.382</td> </tr> <tr> <td>0147-0</td> <td>.563</td> </tr> </tbody> </table>	Basic Part Number	Length A	0133-0	.382	0147-0	.563
Basic Part Number	Length A														
0132-0	.273														
0135-0	.183														
Basic Part Number	Length A														
0133-0	.382														
0147-0	.563														

<h3>SPECIFICATIONS</h3> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 1X - XX - XX - XX - 04 - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <ul style="list-style-type: none"> <li>01 200μ" TIN/LEAD OVER NICKEL</li> <li>◇ 80 200μ" TIN OVER NICKEL (RoHS)</li> <li>◇ 15 10μ" GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>SPECIFY CONTACT FINISH:</b></p> <ul style="list-style-type: none"> <li>02 100μ" TIN/LEAD OVER NICKEL</li> <li>◇ 84 100μ" TIN OVER NICKEL (RoHS)</li> <li>◇ 27 30μ" GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>SELECT CONTACT</b></p> <p>#30 or #32 CONTACT (DATA ON PAGES 218 &amp; 219)</p>
--	---



Downloaded from Elcodis.com electronic components distributor