

<h3>4011</h3> <p>4011-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole</p>	<h3>1801</h3> <p>1801-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole Shell is Ph. Br. Alloy 544 (B2)</p>	<h3>1001</h3> <p>1001-0-15-XX-3X-XX-04-0 Press-fit in 1,45 mounting hole</p>	<h3>0156</h3> <p>0156-0-18-XX-30-XX-04-0 Self-retention socket pin 0,97-1,09 hole prior to soldering</p>
---	---	---	---

<h3>0255</h3> <p>0255-0-15-XX-30-XX-04-0 Solder mount in 0,56 min. mounting hole</p>	<h3>1109</h3> <p>1109-0-15-XX-30-XX-04-0 Hex press-fit in 1,45 plated thru hole</p>	<h3>3013</h3> <p>3013-0-15-XX-32-XX-04-0 Press-fit in 1,45 mounting hole</p>	<h3>0134</h3> <p>0134-0-15-XX-3X-XX-04-0 Press-fit in 1,45 mounting hole</p>
---	--	---	---

<h3>0132/0135</h3> <p>013X-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0132-0</td> <td>6,93</td> </tr> <tr> <td>0135-0</td> <td>4,65</td> </tr> </tbody> </table>	Basic Part Number	Length A	0132-0	6,93	0135-0	4,65	<h3>0133/0147</h3> <p>01XX-0-15-XX-30-XX-04-0 Press-fit in 1,5 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0133-0</td> <td>9,7</td> </tr> <tr> <td>0147-0</td> <td>14,3</td> </tr> </tbody> </table>	Basic Part Number	Length A	0133-0	9,7	0147-0	14,3
Basic Part Number	Length A														
0132-0	6,93														
0135-0	4,65														
Basic Part Number	Length A														
0133-0	9,7														
0147-0	14,3														

<h3>SPECIFICATIONS</h3> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - XX - XX - 04 - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µmTIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p>SPECIFY CONTACT FINISH: →</p> <p>02 2,54µm TIN/LEAD OVER NICKEL ◇ 84 2,54µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p>SELECT CONTACT #30 or #32 CONTACT (DATA ON PAGES 218 & 219)</p>
--	--

Downloaded from Elcodis.com electronic components distributor