

0338	0378	6002	7009
<p><b>0338-0-15-XX-15-XX-10-0</b> Solder mount in 1,45 min. mounting hole</p>	<p><b>0378-0-15-XX-15-XX-10-0</b> Solder mount in 2,08 min. mounting hole</p>	<p><b>6002-0-19-XX-15-XX-10-0</b> Solder mount in 1,5 min. mounting hole</p>	<p><b>7009-0-19-XX-15-XX-10-0</b> Press-fit in 1,6 mounting hole</p>

0339			
<p><b>0339-0-15-XX-15-XX-10-0</b> Solder mount in 1,45 min. mounting hole</p>			

--	--	--	--

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES TOLERANCES ON:</b> LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 1X - XX - 15 - XX - 10 - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b> →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL              ◇ 80 5,08µm TIN OVER NICKEL (RoHS)              ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p><b>SPECIFY CONTACT FINISH:</b> →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL              ◇ 80 5,08µm TIN OVER NICKEL (RoHS)              ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p><b>CONTACT</b> #15 CONTACT (DATA ON PAGE 220)</p>
---	---

