

<p>1305</p> <p>1305-0-15-XX-47-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p>1306</p> <p>1306-0-15-XX-47-XX-04-0 Press-fit in 1,55 mounting hole.</p>	<p>7305</p> <p>7305-0-15-XX-47-XX-10-0 Solder mount in 1,52 min. mounting hole Also available on 8mm wide carrier tape: 6,000 parts per 330mm reel. Order as: 7305-0-57-XX-47-XX-10-0</p>	<p>0400</p> <p>0400-0-15-XX-47-XX-04-0 Press-fit in 1,7 mounting hole.</p>
--	---	---	--

<p>0335</p> <p>0335-0-15-XX-47-XX-04-0 Hex press-fit in .1,63 plated thru hole</p>	<p>4614</p> <p>4614-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02±0,08 plated hole. For 1,52→2,54 thick board.</p>	<p>4615</p> <p>4615-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02±0,08 plated hole. For 2,29→3,30 thick board.</p>	<p>7614</p> <p>7614-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02±0,08 plated hole. For 1,52→2,54 thick board.</p>
--	---	---	---

<p>8401</p> <p>8401-0-15-XX-47-XX-04-0 Hex press-fit in 1,6 plated thru hole</p>	<p>2400</p> <p>2400-0-15-XX-47-XX-04-0 Press-fit in 1,68 mounting hole.</p>	<p>6857</p> <p>6857-0-15-XX-47-XX-10-0 Press-fit in 1,55 mounting hole.</p>	<p>9393</p> <p>9393-0-15-XX-47-XX-10-0 Press-fit in 1,70 mounting hole.</p>
--	---	---	---

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - XX - XX - 47 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µmTIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS) <p>CONTACT</p> <p>#47 CONTACT (DATA ON PAGE 221)</p>
---	---