

| 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 19003 | | | | | | |
|-----------------------------|---------------------------|----------------------------------|--------------------------------|----------------------------|--------------------------|----------------|-----------------------|------------------|--------------|-----------|--------------|----------|-----------|----------|------------------|
| LOOSE PIECE MATERIAL NUMBER | LOOSE PIECE ENGRNG NUMBER | CONTINUOUS STRIP MATERIAL NUMBER | CONTINUOUS STRIP ENGRNG NUMBER | MYLAR TAPE MATERIAL NUMBER | MYLAR TAPE ENGRNG NUMBER | WIRE RANGE AWG | FITS MALE TAB SIZE | INSULATION COLOR | STOCK THICK. | "A" MAX. | "B" (F) MIN. | "C" MAX. | "D" MWID | "E" MAX. | "H" ±.02/0.5 (F) |
| 190030071 | M-2212 | 190030106 | M-2212C | 190030073 | M-2212T | 26-24 | .250x.032 (6.35x0.81) | YELLOW | .016/0.41 | .86/21.8 | .028/0.71 | .38/9.7 | .075/1.90 | .18/4.6 | 1.42/35.9 |
| 190030064 | M-2210 | 190030103 | M-2210C | 190030067 | M-2210T | 26-24 | .187x.020 (4.75x0.51) | YELLOW | .016/0.41 | .78/19.8 | .028/0.71 | .32/8.1 | .075/1.90 | .16/4.1 | 1.38/34.9 |
| 190030068 | M-2211 | 190030104 | M-2211C | 190030070 | M-2211T | 26-24 | .187x.032 (4.75x0.81) | DK YELLOW | .016/0.41 | .78/19.8 | .028/0.71 | .32/8.1 | .075/1.90 | .16/4.1 | 1.38/34.9 |
| 190030001 | AA-2201 | 190030105 | AA-2201C | 190030003 | AA-2201T | 22-18 | .250x.032 (6.35x0.81) | SALMON | .016/0.41 | .86/21.8 | .056/1.42 | .38/9.7 | .135/3.43 | .18/4.6 | 1.42/35.9 |
| 190030036 | AA-2213 | 190030109 | AA-2213C | 190030074 | AA-2213T | 22-18 | .205x.020 (5.21x0.51) | SALMON | .016/0.41 | .78/19.8 | .056/1.42 | .32/8.1 | .135/3.43 | .16/4.1 | 1.38/34.9 |
| 190030038 | AA-2214 | 190030110 | AA-2214C | 190030075 | AA-2214T | 22-18 | .205x.032 (5.21x0.81) | PINK | .016/0.41 | .78/19.8 | .056/1.42 | .32/8.1 | .135/3.43 | .16/4.1 | 1.38/34.9 |
| 190030001 | AA-2201 | 190030105 | AA-2201C | 190030003 | AA-2201T | 22-18 | .250x.032 (6.35x0.81) | SALMON | .016/0.41 | .86/21.8 | .056/1.42 | .38/9.7 | .135/3.43 | .18/4.6 | 1.42/35.9 |
| 190030017 | AA-2203 | 190030108 | AA-2203C | 190030020 | AA-2203T | 22-18 | .187x.032 (4.75x0.81) | PINK | .016/0.41 | .78/19.8 | .056/1.42 | .32/8.1 | .135/3.43 | .16/4.1 | 1.38/34.9 |
| 190030024 | AA-2204 | 190030097 | AA-2204C | 190030026 | AA-2204T | 22-18 | .110x.020 (2.79x0.51) | SALMON | .012/0.30 | .78/19.8 | .056/1.42 | .23/5.9 | .135/3.43 | .15/3.8 | 1.39/35.3 |
| 190030030 | AA-2205 | 190030098 | AA-2205C | 190030032 | AA-2205T | 22-18 | .110x.032 (2.79x0.81) | PINK | .012/0.30 | .78/19.8 | .056/1.42 | .23/5.9 | .135/3.43 | .15/3.8 | 1.39/35.3 |
| 190030040 | BB-2206 | 190030041 | BB-2206C | 190030042 | BB-2206T | 16-14 | .250x.032 (6.35x0.81) | BLUE | .016/0.41 | .86/21.8 | .079/2.00 | .38/9.7 | .160/4.06 | .18/4.6 | 1.42/35.9 |
| 190030062 | BB-2215 | 190030085 | BB-2215C | 190030077 | BB-2215T | 16-14 | .205x.020 (5.21x0.51) | BLUE | .016/0.41 | .78/19.8 | .079/2.00 | .32/8.1 | .160/4.06 | .17/4.3 | 1.41/35.7 |
| 190030063 | BB-2216 | 190030086 | BB-2216C | 190030078 | BB-2216T | 16-14 | .205x.032 (5.21x0.81) | AQUA | .016/0.41 | .78/19.8 | .079/2.00 | .32/8.1 | .160/4.06 | .17/4.3 | 1.41/35.7 |
| 190030050 | BB-2207 | 190030051 | BB-2207C | 190030052 | BB-2207T | 16-14 | .187x.020 (4.75x0.51) | BLUE | .016/0.41 | .78/19.8 | .079/2.00 | .32/8.1 | .160/4.06 | .17/4.3 | 1.41/35.7 |
| 190030056 | BB-2208 | 190030057 | BB-2208C | 190030058 | BB-2208T | 16-14 | .187x.032 (4.75x0.81) | AQUA | .016/0.41 | .78/19.8 | .079/2.00 | .32/8.1 | .160/4.06 | .17/4.3 | 1.41/35.7 |
| 196060002 | C-2293 (F) | 196060001 | C-2293C (F) | 196060003 | C-2293T (F) | 12-10 | .250x.032 (6.35x0.81) | YELLOW | .018/0.46 | 1.03/26.1 | .117/2.97 | .38/9.7 | .235/5.97 | .22/5.6 | 1.53/38.9 |

CONTINUOUS PLASTIC STRIP

WIRE STOP

NEMA DETENT LOCATION

PARTS ON TAPE

SALES DRAWING

NOTES:

- MATERIAL: TERMINAL: BRASS
PLATING: ELECTRO-TIN
FERRULE: BRASS
PLATING: ELECTRO-TIN
INSULATION: NYLON 6/6 94V-2.
COLOR: SEE CHART
- MWID = MAXIMUM WIRE INSULATION DIAMETER
- PARTS ARE ROHS COMPLIANT.

| ID/TAPE TOLERANCES | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE | | SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION |
|--|-----------------|---|-------|-----------------|------------|-----------|--|---------------------------|
| | | mm | INCH | IN/MM | INCH | | | |
| EC NO: WNA2011-0433 | ▽=0 ▽=0 | 4 PLACES | ± --- | ± --- | DRAWN BY | DATE | INSULKRIMP FEMALE FIQD STANDARD FLARE | MOLEX INCORPORATED |
| 1 DRW: WETHRODAHL 2011/02/28 | | 3 PLACES | ± --- | ± --- | BRE | 02/03/20 | | |
| CHKD: JMCNEIL 2011/02/28 | | 2 PLACES | ± --- | ± --- | CHECKED BY | DATE | | |
| APPR: JMCNEIL 2011/03/03 | | 1 PLACE | ± --- | ± --- | HEB | 02/03/20 | | |
| DESCRIPTION | | ANGULAR ± ---° | | APPROVED BY | DATE | | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | MATERIAL NO. | | DOCUMENT NO. | | SHEET NO. | | |
| | | SEE CHART | | SD-19003-005 | | 1 OF 1 | | |
| | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | | |