



- 1 CONTINUOUS STRIP ON REELS.
- 2 STRESS RELIEVE PART, WILL HAVE HIGHER INSERTION FORCES.
- 3 PRELIMINARY - NOT FOR PRODUCTION

TIN 0.002032 [0.00080] MIN	2.29-3.94 [0.90-.155] DIA	[#18-#14] AWG	2 3 63854-3
TIN 0.002032 [0.00080] MIN	2.29-3.94 [0.90-.155] DIA	[#18-#14] AWG	63854-2
-	2.29-3.94 [0.90-.155] DIA	[#18-#14] AWG	63854-1
FINISH	INSULATION RANGE	WIRE SIZE	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNER: J.R. RUTH 4/28/95
 CHECKER: M.S. FEHNER 4/28/95
 APPROVED: R. REINER 4/28/95

TE Connectivity

RECEPTACLE, POSITIVE LOCK, 6.35 [250] SERIES

APPLICATION SPEC: 114-2061
 SIZE: A200779 C=63854
 WEIGHT: -

MATERIAL: H06 BRASS
 FINISH: SEE TABLE

CUSTOMER DRAWING

SCALE: 5:1 SHEET: 1 of 1 REV: L1