


DO NOT SCALE METRIC THIRD ANGLE PROJECTION

NOTES:
 ▲ FOR USE ON MINIATURE APPLICATORS (LEFT-RIGHT FEED)
 ▲ PH. BRONZE ELONGATION A50 ≥ 20%.
 ▲ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	▲ PRE-TINPLATED	BRASS	160859-8	
	▲ PRE-TINPLATED	Ph BRONZE	160859-7	
	▲ UNPLATED	Ph BRONZE	160859-6	
	▲ SILVERPLATED	Ph BRONZE	160859-5	
	▲ TINPLATED	Ph BRONZE	160859-4	
	▲ UNPLATED	Ph BRONZE	160859-3	
	▲ UNPLATED	BRASS	160859-2	
	▲ UNPLATED	BRASS	160859-1	
	PLATING	PLATING	MATERIAL	PARTNUMBER

G2	REV PER ECO-10-000444	KK	AEG	08JAN10	CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED © COPYRIGHT 19- BY AMP ITALIA S.p.A. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED AND/OR PATENTS PENDING. RELEASED FOR PUBLICATION - ,19 - AMP AMP ITALIA S.p.A. Corso F.Lli Cervi, 15 COLLEGNO (TORINO)
G1	ET00-0358-99	H.Y.	22	14 NOV 99	
G	EH-2170-98	-	-	28 JAN 98	
G	EH-1981-98	D.K.	A.B.	25 NOV 98	
F	EH-0034-94	DK	PB	03-02-94	
E	EH-0017-94	DK	PB	19-01-94	
D	H-9671	JVL	AB	23-03-92	
LTR.	REVISION RECORD	DR.	CHK.	DATE	NAME
DR.: J.V.LIEPHT.	CHK.: A.BIJNEN.	APP.: L.V.SOEST.	DWG.No.	C-160859	FASTIN-FASTON® Connector, .250" sr. TAB CONTACT.
DATE: 23 MAR 1992	DATE:	DATE:	REV.LTR.	G2	SHEET 1 OF 1

WIRE RANGE : 0,5-1,0 mm²
 INSULATION RANGE : 1,4-2,3mm DIA.



88-128 ... 8 7 6 5 4 3 2 1