



WIRE RANGE :
>2,5-4,0 mm²
INSULATION RANGE :
3,3-4,5 DIA.

DO NOT SCALE
DIMENSIONS IN mm

METRIC



NOTES:

- △ FOR USE ON MINIATURE APPLICATORS (LEFT-RIGHT FEED) AND STANDARD APPLICATORS (RIGHT-LEFT FEED).
- △ REELED WITH PAPER COVER.
- △ SPLICE FREE CODE 115-10003.1
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

GENERAL TOLERANCES ±0.3

OBSOLETE	△	PRE-TINPLATED	PH.BRONZE	6-160913-8
	△	PRE-TINPLATED	BRASS	6-160913-7
	△	TINPLATED	PH.BRONZE	160913-4
	△	UNPLATED	PH.BRONZE	160913-3
	△	TINPLATED	BRASS	160913-2
	△	UNPLATED	BRASS	160913-1

NOTES	FINISH	MATERIAL	PARTNUMBER
E2 ECO-09-025699	KK	AEG 180EC09	CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED
E1 4,4 was 4,1	J.L	J.L 17JUL/2006	© COPYRIGHT 19- BY AMP HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING.
E ES00-0008-03	JL	JL 17JAN03	THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION 19
D ES00-0065-01	JC	JL 19JUN01	Tyco Electronics Corporation Barcelona, Spain
C ES00-0043-01	JC	RS 2MAY01	
B EH-1045-97	D.K.	R.V. 26 SEP 97	NAME
A EH-0168-94	DK	PB 21-06-94	.250 SRS FAST-IN-ON RECEPTACLE
LTR. REVISION RECORD	DR.	CHK.	DATE
DR.: L.V. HEIJDEN	CHK.: A.BIJNEN	APP.: L.V. SOEST	DWG.No. 160913
DATE: 02-07-87	DATE: 10-08-87	DATE: 24-08-87	REV.LTR. E2
			SHEET 1 of 1