


SCALA NON IMPERATIVA
(DO NOT SCALE)
DIMENSIONI IN mm
(DIMENSIONS IN mm)

METRIC

PROIEZIONE EUROPEA
(EUROPEAN PROJECTION)

1) STATO DI FORNITURA
(SUPPLY CONDITION)

P/N 280079-1
P/N 280079-2
P/N 280079-3



P/N 1-280079-1
P/N 1-280079-2

2) NON DISPONIBILE DA AMP ITALIA
PRODUZIONE AMP SPAGNA
(NOT AVAILABLE FROM AMP ITALY
AMP SPAIN PRODUCTION)

3) STATO DI FORNITURA
(SUPPLY CONDITION)



SENSO DI USCITA DEL TERMINALE
DALLA BOBINA
(DIRECTION OFF
TOP OF REEL)

4) P/N CON ELEVATA FORZA DI ESTRAZIONE
(P/N SUITABLE FOR HIGH EXTRACTION FORCE APPLICATION)
5) SPECIFICA DI PRODOTTO 108-20019
(PRODUCT SPEC. 108-20019)

6) INCLINAZIONE 45° MAX. BENT PERMESSA
PER LA PRIMA MANOVRA DI ACCOPPIAMENTO
CON BLOCCHETTO PORTA FEMMINA.
(45° MAX. PERMISSIBLE FOR THE FIRST MATING
WITH THE INSULATION SLEEVE).

7) SUPERSEDED BY P/N 160739-6

8) OBSOLETE PARTS: OBSOLETE CIS STREAMLINING
PER D.RENAUD/D.SINISI

BRASS TIN PLATED	1-280079-5/3	-
STEEL NICKEL PLATED	280079-3	-
BRASS TIN PLATED	280079-2	1-280079-2
BRASS (UNPLATED)	280079-1	1-280079-1
MATERIAL/FINISH	FOR USE ON STD APPLICATOR (RIGHT TO LEFT FEED)	FOR USE ON MINI APPLICATOR (LEFT TO RIGHT FEED)

CUSTOMER DWG. FOR REFERENCE ONLY DISEGNO PER CLIENTE SOLO PER RIFERIMENTO

THIS DRAWING IS UNPUBLISHED	RELEASE FOR PUBLICATION	19
© COPYRIGHT 1980 BY AMP INCORPORATED, HARRISBURG, PA. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENT AND/OR PATENT PENDING.		
TOLLERANZE, SE NON DIVERSAMENTE SPECIFICATE (DIMENSIONS, UNLESS OTHERWISE SPECIFIED)	DIAN. ISOLANTE (INS. DIA. RANGED)	RANGO FILO (WIRE RANGED)
± 0.3	3.0-4.3mm	0.8-2.5mm ²
ANGOLI (ANGLES)	SCALA (SCALED)	
± 2°	-	

AMP AMP ITALIA S.p.A.
Corso F.lli Casati, 16
COLLENO (TORINO)

Y1	ECO-09-026346	KK	AEG	± 0.3
Y	ECR-06-012970			
W1	ADD'S VIEW AND NOTE 6 ET00-0082-01	H.Y.	2000	DIS. R. FABRIS 23 FEB 00
W	OBSOLETE PARTS, ET00-0093-99	H.Y.	2000	CONT. C. TARTARI
U1	REVISED & REDRAWN, ET00-0058-00	R.F.	2000	
REV.	REVISIONI (REVISION RECORD)	DIS. DATA (DR)	APP. DATE	

DESCRIZIONE (DESCRIPTION) FASTON® Connector, .250" sr. PIGGY-BACK REC. CTC. (STRIP FORM)
LOC. SIZE (LOC. DIM.) I A3 C-280079
REV. Y1
FOLIO (SHEET) 1 DI 1

DISTRIBUZIONE: GRIP (DET.)