

- Products**
- Products Overview
 - Product Search**
 - Evaluate
 - FAQ's
 - Design a Solution
 - Part Drawings
 - PDF-Right Angle ..
 - How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click to remove) Search Tips

Part Number > DNFR14-250B-L

Your search criteria matched only one product, shown below

DNFR14-250B-L

- Right angle design for use in limited space applications
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Disconnects available in common industry tab sizes
- Longer barrel design for use with Panduit standard disconnect tool



▪ Part Number	DNFR14-250B-L
▪ RoHS Compliancy Status	Compliant
▪ Note	DNFR14-250B-L replaces DNFR14-250B-C
▪ Part Description	Female Disconnect, right angle, nylon insulated, 16 – 14 AWG, .250 x .032 tab size.
▪ Product Type	Disconnects
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ Depth (In.)	0.63
▪ Depth (mm)	16.0
▪ Height (In.)	0.20
▪ Height (mm)	5.1
▪ Length (In.)	0.78
▪ Length (mm)	19.8
▪ Width (In.)	0.36
▪ Width (mm)	9.1
▪ CE Compliant	No
▪ Max. Ins.	0.155
▪ Max. Ins. (mm)	3.95
▪ Panduit Color Code	Blue
▪ Pricing Description	Female Disconnect, right angle, nylon insulated, 16 - 14 AWG, .250 x .032 tab size
▪ Tab Size (In.)	0.250 x 0.032
▪ Tab Size (mm)	6.3 x 0.8
▪ Tool	CT-1525‡, CT-2500‡
▪ Wire Range	16 – 14 AWG
▪ Wire Range (mm²)	1.5 – 2.5
▪ Min. Order UOM	PC
▪ Min. Order Qty.	50
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.