V DATE	BY	СНК	DESCRIPTI	ON	ECN	SCALE N/A DRAWING NO / CAD FILE LCA2-14-CUST	
01 10/10 JHNU JHNU REMOVED NAVY NUMBER FROM STAMP		AMP		LCA2-14-Q Copper Lug - One-Hole, Standard Barrel			
-	+						
						PANDUIT CORP. TINLEY PARK, ILLINOI	
	_			.10±.0			
	С	ERTIFIEI	D LISTED Wire Connector	1	- 		
				 	1		
Die Index on Barrel		_				.31±.01 .42±.01	
Alternate Industry			(10)	Wire inspection	on window—		
Panduit Die Index No. on Barrel		ex No.	P33		.88±.04 ————————————————————————————————————		
Panduit Color Code on Barrel			BROWN				
C.S.A Certified Wire Connector			Yes	1			
UL Temperature Rating			90°C	-		1.77±.06	
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.25±.04	PANDUIT (®)	.38 R Ref Color coded barrel markings COVER COMM DIE 25 ST COVER COMM	
Stud Size			1/4 in.	.60±.04			
Wire Strip Length			15/16 in.				
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	<u> </u>			
Wire Size			2 AWG				
Plating			Electro-Tin				
Material			High Conductivity Seamless Copper Tube				