MC	aterial			High Conductivity Seamless Copper Tube					
Plc	ating			Electro-Tin					
Wire Size				1 AWG		/	38 R Ref		
Wire Type Wire Strip Length			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	<u> </u>	(#) 75 75		Color coded barrel markings		
		1	15/16 in.			D 4-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1			
Stud Size				1/4 in.	.70±.04	$\left(- \right - \right)$	CA1-		0 H P
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	PA	3 z		PANDUIT GREEN DIE P37 (11)		
	UL Temperature Rating			90° C	.25±.04 —-	-	.27±.02 DIA		
	C.S.A Certified Wire Connector			Yes	1.79±.06 ─				
	nduit Co Barrel	olor C	ode	GREEN					
	Panduit Die Index No. on Barrel Alternate Industry Die Index No. () on Barrel		ex No.	P37	Wire inspection window————————————————————————————————————				
Die				(11)	wire inspection	i window —			
		CI	ERTIFIE	D LISTED Wire Connector	<u> </u>			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	.36±.01 .47±.01
					11±.	01			
							PANDU	CORP.	TINLEY PARK, ILLINOI
0	9/02 SAB DRL RELEASED			RELEASE)	10318	Copper Lu	LCA1-14-I	
-	. ,			11227 1021					