Mat	terial			High Conductivity Seamless Copper Tube						
Plat	ling			Electro-Tin			_	47 R Ref		
Wire	Wire Size			1 AWG						
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric					Color coded barrel marking	5	
Wire	Wire Strip Length			15/16 in.			$\overline{2}$		<b>UI</b>	22 (11)
Stud Size				3/8 in.	.70±.04		╤──┼╴			
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	<	• .36±.04 •		GREEN P			
UL Temperature Rating			90 ° C	:						
C.S.A Certified Wire Connector			Yes					1.99±.06	*	
Panduit Color Code on Barrel			ode	GREEN						
Panduit Die Index No. on Barrel		ex No.	P37			/ entry			Beveled wire entry	
Alternate Industry Die Index No. ( ) on Barrel				(11)	Wiem	spection	window –			
					· 					.36±.01 .47±.01
		CI	RTIFIED	) LISTED Wire Connector	 11±	01	i			
									1052	
										TINLEY PARK, ILLINOI
			DPI				10318	LCA1-38-E Copper Lug - One-Hole, Standard Barrel		
0 9/02 SAB DRL		DKL	RELEASED DESCRIPTION			10318	SCALE N/A DRAWING NO / CAD FILE LCA 1-38-CUST			