		NO TID	LD OIL		D IN ANY WAY DETRIMENTAL TO THE INT 1		
M	laterial			High Conductivity Seamless Copper Tube			
Ρl	ating			Electro-Tin		.27±.02 DIA	
Wire Size			14 - 10 AWG STR, 12 - 10 AWG SOL	/			
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric		.27±.02		
W	/ire Strip	Length	٦	9/16 in.			
Stud Size			1/4 in.				
UL Listed Wire Connector UL Temperature Rating C.S.A Certified Wire Connector Panduit Color Code on Barrel Panduit Die Index No. on Barrel			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.25±.04 .50	0±.02		
			90°C	┃	.63±.02 —		
			Yes		1.93±.06	Beveled wire	
		ode	N/A		/	entry	
		ex No.	N/A				
Alternate Industry Die Index No. () on Barrel				N/A	Wire inspe	ction window	<u> </u>
		CI	ERTIFIE	D LISTED Wire Connector	.05±.01	.13±.01	22±.01
							ey park, illinois
-						LCC10-14JAW-L	
1	12/04	12/04 JHNU JHNU REVISED WIRE			SIZE 12305	Copper Lug - Slotted Two-Hole, Long	Barrel with Windo
ΞV	DATE	BY	снк	DESCRIPTIO	N ECN	SCALE DRAWING NO / CAD FILE	LCC10-14JAW-CUST