ΕV	DATE	BY	СНК	DESCRIPTION	DN	ECN	SCALE DRAWING NO / CAD FII	LCC6-14JAW-CUST
00	9/04	JHNU	CSH	RELEASED		12021	LCC6-14JAV Copper Lug - Slotted Two-Hole, Lo	ong Barrel with Windo
								TINLEY PARK, ILLINOIS
		CE	ERTIFIED	D LISTED Wire Connector	.08±.01			1
Alternate Industry Die Index No. () on Barrel			ту 	(7)	Wire	nspection	on window	.22±.01 .31±.01
	anduit Di n Barrel	e Inde	ex No.	P24			1.07±.04	Beveled wire
Panduit Color Code on Barrel			ode	BLUE				
C.S.A Certified Wire Connector			Yes	-		2.49±.06	<b>-</b>	
	L Tempei ating	ature		90°C		.63±.	.02 —	
UL Listed Wire Connector				Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.25±.04	50±.02		
Stud Size				1/4 in.	.48±.04	6 STR CU	BANE DE	<b>I</b>
W	/ire Strip l	ength	1	1-1/8 in.	.48±.04	C C C A	ANDUIT ANDUIT	Í
Wire Type				Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric			.27±.02	Color coded barrel markings
Wire Size				6 AWG			.27±.02 DIA	
PΙ	ating			Electro-Tin				
IVI	laterial			High Conductivity Seamless Copper Tube				