



AMP WIRE RANGE	E13288 Listed
12-10 AWG STRANDED	12-10 AWG STRANDED
LR7189 Certified	MILITARY P/N AND CLASS
NOT CERTIFIED	NOT APPLICABLE

△ STAMP AMP 12-10* APPROX AS SHOWN

AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		MAX RECOMMENDED OPERATING TEMPERATURE: 170°C MAX
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752	VOLTAGE RATING: NOT APPLICABLE
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111	WIRE CROSS SECTIONAL AREA RANGE: 2.62-6.54mm ² [5.180-13.100] CIR MILS STRANDED
FOR ORDER ENTRY	1-800-526-5142	

DO NOT SCALE PRINT.
UNLESS SPECIFIED OTHERWISE DIMENSIONS ON DRAWINGS ON 1/8" PAPER DEC 4 - ANGLES
WATERBURY
COPPER PER ASTM B-152 ANNEALED
TIN PLATE
0.00254 [0.00100] MIN THK PER MIL-T-10727

OR 1-29-83 TA BRINKMAN	NAME	AMP
CHK 1-29-83 DA PATTERSON	TERMINAL, RECTANGULAR TONGUE, BUDGET	AMP Incorporated Harrisburg, PA 17105-3608
APPD 1-29-83 DE MILLER	SIZE	00779
APPD 1-29-83 J. HECOLEY	CASE CODE	331269
PRODUCT SPEC	DRAWING NO	331269
APPLICATION SPEC	SCALE	8:1
WEIGHT	SHEET	1 OF 1