1010	aterial			High Conductivity Seamless Copper Tube					
Plc	ating			Electro-Tin					
Wire Size Wire Type Wire Strip Length			8 AWG	31 R Ref					
			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	<u> </u>			Color coded barrel markings		
		ì	5/8 in.		(5)	8 STR CU LCA8-10	<b>=</b> 5		
Stud Size				#10			41+ 04   C	PANDUII	
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	Z Z Z	3	.20±.02 DIA	PANDUI		
	UL Temperature Rating			90° C	.23±	±.04			
	C.S.A Certified Wire Connector			Yes	-	1.25±.06 →			-
Panduit Color Code on Barrel  Panduit Die Index No. on Barrel  Alternate Industry Die Index No. () on Barrel		ode	RED						
		ex No.	P21	Wire inspection window —					
			N/A					entry	
		(			, <u> </u>				.18±.01 .27±.01
		CI	ERTIFIEC	D LISTED Wire Connector	.08±.	)1			
							PANDUI	CORP.	TINLEY PARK, ILLINOI
								LCA8-10-L	
0	9/02	SAB	DRL	RELEASEI	)	10318	Copper Lug	g - One-Hole, S	Standard Barrel