Materia	al		High Conductivity Seamless Copper Tube		
Plating			Electro-Tin	60 R Ref	
Wire Size			1/0 AWG	Color coded	
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	barrel markings	
Wire Strip Length		า	1.0 in.	PANDUIT PINK DIE PAZ (12) PINK DIE PAZ (13) PINK DIE PAZ (13) PINK DIE PAZ (13) PINK DIE PAZ (13)	
Stud Size			1/2 in.		
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.47±.04	
UL Temperature Rating			90°C		
C.S.A Certified Wire Connector			Yes		
Panduit Color Code on Barrel		ode	PINK		
Panduit Die Index No. on Barrel		ex No.	P42		
Alternate Industry Die Index No. () on Barrel			(12)	Wire inspection window	
	CE		D LISTED Wire Connector	.12±.01	
				PANDUIT CORP. TINLEY PARK, ILLINOI	
1/08	08 DRL	DRL	REMOVED NAVY NUMBE	EROM STAMP LCA1/0-12-X Copper Lug - One-Hole, Standard Barrel	
			DESCRIPTIC		