



WIRE RANGE	E13288 Listed
22-16 AWG STRANDED	22-16 AWG STRANDED
LR7189 Certified	MILITARY P/N AND CLASS
NOT CERTIFIED	NOT APPLICABLE

△ STAMP AMP 22-18* APPROX AS SHOWN
 22-16 TERMINALS ARE STAMPED 22-18 IN ACCORDANCE WITH MILITARY SPECIFICATION MIL-T-7928, COMMERCIAL WIRE RANGE IS 22-16

**AMP INCORPORATED
 CUSTOMER SERVICE SYSTEMS**

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111
FOR ORDER ENTRY	1-800-526-5142

MAX RECOMMENDED OPERATING TEMPERATURE:	170°C MAX
VOLTAGE RATING:	NOT APPLICABLE
WIRE CROSS SECTIONAL AREA RANGE:	0.26-1.65mm ² (S09-3,260) CIR HILLS STRANDED

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS ARE IN MILLIMETERS ON 1 P/LC DEC # - ANGLES	FINISH	TIN PLATE
	THK PER MIL-1-10727	

DR TA BRINKMAN	CHK 1-27-83
DA PATTERSON	APPD 1-27-83
DE MILLER	APPD 1-27-83
JL HECKLEY	PRODUCT SPEC

NAME	AMP INCORPORATED Harrisburg, PA 17105-3608
TERMINAL, RING TONGUE, BUDGET	
SIZE	CASE CODE 00779
SCALE	DRAWING NO 31087
WEIGHT	SHEET 1 OF 1

31087
 PART NO

CUSTOMER DRAWING

LOC	QTY	REV	DATE	APPD
G	14	A	REVISED PER 0720-0230-93	

REVISIONS	DESCRIPTION	DATE	APPD

31087