

10		9		8		7		6		5		4		3		2		19070	
LOOSE PIECE				TAPE MOUNTED				SPECIFICATIONS											
MATERIAL NUMBER	ALTERNATE NUMBER	MATERIAL NUMBER	ALTERNATE NUMBER	HOUSING COLOR	STUD SIZE	"S" ±.005/(0.13)	"W" MAX.	"C" MIN.	"L" MAX.	"ID" MIN.	STOCK THICKNESS REFERENCE	"H" ±.020/.051							
190700005	AA-220-02X	190700006	AA-220-02XT	RED	2	.094/(2.39)													
190700007	AA-220-04X	190700008	AA-220-04XT	RED	4	.119/(3.02)	.235/(6.00)	.157/(3.99)	.709/(18.01)	.062/(1.57)	.028/(0.71)								
190700009	AA-220-06X	190700010	AA-220-06XT	RED	6	.146/(3.71)													
190700011	AA-221-06X	190700012	AA-221-06XT	RED	6	.146/(3.71)													
190700013	AA-221-08X	190700014	AA-221-08XT	RED	8	.173/(4.39)													
190700015	AA-221-10X	190700017	AA-221-10XT	RED	10	.198/(5.03)	.322/(8.18)	.270/(6.86)	.866/(22.00)	.062/(1.57)	.028/(0.71)	.980/(24.89)							
190700019	AA-221-209X	190700020	AA-221-209XT	RED	M5	.209/(5.18)													
190700021	AA-222-10X	190700022	AA-222-10T	RED	10	.198/(5.03)													
190700023	AA-222-14X	190700024	AA-222-14XT	RED	14	.265/(6.73)	.477/(12.11)	.386/(9.80)	1.060/(26.92)	.062/(1.57)	.028/(0.71)								
		190700601	AA-222-14XT-BK	BLACK	14	.265/(6.73)													
190700026	AA-222-56X	190700027	AA-222-56XT	RED	5/16"	.328/(8.33)													
190700029	AA-226-10X	190700030	AA-226-10XT	RED	10	.198/(5.03)													
190700031	AA-226-14X	190700032	AA-226-14XT	RED	14	.265/(6.73)	.544/(13.82)	.552/(14.02)	1.259/(31.98)	.055/(1.40)	.031/(0.79)	1.172/(29.77)							
190700036	AA-226-56X	190700037	AA-226-56XT	RED	5/16"	.328/(8.33)													
190700033	AA-226-38X	190700035	AA-226-38XT	RED	3/8"	.390/(9.91)													
190700038	AA-232-04X	190700039	AA-232-04XT	RED	4	.119/(3.02)													
190700040	AA-232-06X	190700042	AA-232-06XT	RED	6	.146/(3.71)	.264/(6.70)	.240/(6.10)	.807/(20.50)	.062/(1.57)	.028/(0.71)								
190700044	AA-232-08X	190700045	AA-232-08XT	RED	8	.173/(4.39)													
190700051	AA-233-10X	190700052	AA-233-10XT	RED	10	.198/(5.03)	.283/(7.20)	.240/(6.10)	.816/(20.73)	.062/(1.57)	.028/(0.71)								

NOTE(S):
1. MATERIAL: COPPER
PLATING: ELECTROPLATE TIN
2. DELETED
3. INSULATION: MOLDED PVC, SEE CHART FOR COLOR (C2)
4. MWID=MAXIMUM WIRE INSULATION DIA.
5. ALL DIMENSIONS IN INCHES (MM).
6. PARTS ARE ROHS COMPLIANT.

TO BOTTOM OF BARREL

SALES DRAWING

REDRAW, ADD BLACK HSG EC NO: WNA2011-0382 DRAWN: ETHRODAHL 2011/01/20 CHKD: JIMACNEILL APPR: JIMACNEILL 2011/02/21 REV: 2	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± .15</td> <td>± .005</td> </tr> <tr> <td>3 PLACES</td> <td>± .10</td> <td>± .003</td> </tr> <tr> <td>2 PLACES</td> <td>± .07</td> <td>± .002</td> </tr> <tr> <td>1 PLACE</td> <td>± .05</td> <td>± .001</td> </tr> <tr> <td colspan="3" style="text-align: center;">ANGULAR ± .5°</td> </tr> </table>		mm	INCH	4 PLACES	± .15	± .005	3 PLACES	± .10	± .003	2 PLACES	± .07	± .002	1 PLACE	± .05	± .001	ANGULAR ± .5°			DIMENSION STYLE IN/MM	SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
			mm	INCH																				
4 PLACES	± .15	± .005																						
3 PLACES	± .10	± .003																						
2 PLACES	± .07	± .002																						
1 PLACE	± .05	± .001																						
ANGULAR ± .5°																								
DRAWN BY: DMYRICK CHECKED BY: HBEITZEL APPROVED BY: RDEROSS DATE: 2005/7/22		TITLE RING TONGUE TERMINAL INSULKRIMP, 200-SERIES 22-18 AWG		MOLEX INCORPORATED																				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART		DOCUMENT NO. SD-19070-003		SHEET NO. 1 OF 1																		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION