THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -.-.-
© COPYRIGHT - By - ALL RIGHTS RESERVED

UOC	DIST
CM	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DRN	APVD
	B1	REVISED PER ECO-11-004820	11MAR11	RK	HMR

1. PARTS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-5.
2. 0.00508 [.000200] MIN BRIGHT TIN-LEAD.
3. WIRE RANGE: 3 mm² (12 AWG).
4. INSULATION RANGE: 2.29 – 3.81 [.090 – .150] DIA.
5. DIMENSIONS IN BRACKETS ARE IN INCHES.
6. 0.00508 [.000200] MIN BRIGHT TIN.





SECTION D–D









SECTION A–A



SECTION B–B



SECTION C–C

METRIC

6	3-794013-1
2	794013-1
FINISH	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCE UNLESS OTHERWISE SPECIFIED: 0 PLC ±, 1 PLC ±, 2 PLC ±, 3 PLC ± 0.13 [.005], 4 PLC ±, ANGLES ±

MATERIAL 0.198 [.0078] PH BRZ

FINISH

DWN S. CARPENTER 01MAR2003
CHK J. ELLIS 01MAR2003
APVD J. ELLIS 01MAR2003
PRODUCT SPEC 114-1016
APPLICATION SPEC
WEIGHT

TE Connectivity

NAME TERMINAL, AMP-IN

SIZE A1 CAGE CODE 00779 DRAWING NO C-794013 RESTRICTED TO –

CUSTOMER DRAWING SCALE 10:1 SHEET 1 OF 1 REV B1

Downloaded from Elcodis.com electronic components distributor